Manufacturer Catalog Number

gs - Bonding Connector Harnesses

gs-a - #6 AWG Stranded Harness Wires

Bonding in Aerial, Buried or Underground Splice Cases, and Ready-Access Enclosures

	<u>Noninsulated</u>			<u>Insulated</u>		
	10" Length	20" Length	22" Length	10" Length	20" Length	22" Length
Electric Motion Company	EM8100-10B.10	EM8100-20B.10	EM8100-22B.10	EM8100-10.10	EM8100-20.10	EM8100-22.10
LSW	LSW 6-10	LSW 6-20	LSW 6-22	LSW 6-10C	LSW 6-20C	LSW 6-22C

Bonding in Buried Plant Housings

	Noninsulated			Insulated		
	6" Length	11" Length	18" Length	6" Length	11" Length	18" Length
Electric Motion Company	EM8100-6B.10	EM8100.11B.10	EM8100-18B.10	EM8100-6.10	EM8100.11.10	EM8100-18.10
LSW	LSW 6-06	LSW 6-11	LSW 6-18	LSW 6-06C	LSW 6-11C	LSW 6-18C

gs-b - #6 AWG Braid

Bonding in Aerial, Buried, or Underground Splice Cases, Ready-Access Enclosures, and Buried Plant Housings

	Noninsulated	Insulated
A.K. Stamping	A1163	-
Electric Motion Company	EM-2050	EM-2051
Excelco	579203-25	-
3M	_{25T} (4)	25/4467 (4)

See page 3.3.1 for notes.

<u>Manufacturer</u> <u>Catalog Number</u>

gs - Bonding Connector Harnesses (Stranded Type Wire)

Buried Service Wire (Bare Metal Shields Only)

gs-a - #14 AWG Insulated Harness Wires

Bonding at Station Protector (Network Interface Device)

	<u>7" Length</u>
Electric Motion Company	EM1407TFFR (1)
Engineered Products Co.	EH-13 (1)
LSW	LSW-5(1)
Preformed Line Products	8000739 (2)
Siecor (CAC)	_{GH-13} (1)

gs-b - #6 AWG Insulated Harness Wires

Bonding in Buried Plant Housings

	<u>15" Length</u>	36" Length	
Electric Motion Company	EM3955-6L/8100-15 (3)	EM3955-6L/8100-36 (3)	

Notes: (1) Harnesses equipped with AMP's #329860 Termi-Foil^R connector at one end for attachment to the bare metal shield of the service wire.

- (2) Harnesses equipped with Preformed Line Products' 8000733 connector at one end for attachment to the bare metal shield of the service wire.
- (3) Harnesses equipped with Electric Motion's EM3955 connector at one end for attachment to the bare metal shield of the service wire.
- (4) When ordering, state 3-inch eyelets.